

GAMME BLACK PUR SINUS



300 W



600 W



1000 W



1500 W



3000 W

Convertisseurs de tension

12 / 220 V & 24 / 220 V

GAMME BLACK



150 W



300 W



600 W



1000 W



1500 W



3000 W



	1		2		3		4		5		6		7		8		9		10		11	
Référence	ACAL202	ACAL402	ACAL204	ACAL404	ACAL207	ACAL405	ACAL211	ACAL407	ACAL216	ACAL416	ACAL231	ACAL409	ACAL605	ACAL705	ACAL606	ACAL706	ACAL607	ACAL707	ACAL608	ACAL708	ACAL609	ACAL709
Volts (V)	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220
Tension d'alimentation	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC	De 11 à 15 V DC	De 22 à 30 V DC
Sortie USB	5 V DC, 500 mA (max)																					
Tension / Fréquence	230 V AC ± 10%, 50 Hz ± 3 Hz												230 V AC ± 10%, 50 Hz ± 0.5 Hz									
Puissance de sortie en continu	150 W		300 W		600 W		1000 W		1500 W		3000 W		300 W		600 W		1000 W		1500 W		3000 W	
Puissance de sortie en pointe	300 W		600 W		1200 W		2000 W		3000 W		6000 W		600 W		1200 W		2000 W		3000 W		6000 W	
Signal de sortie	Sinusoïdale modifiée												Pure sinus THD < 5%									
Rendement	> 80 %																					
Courant de veille	< 0,45 A	< 0,25 A	< 0,45 A	< 0,25 A	< 0,45 A	< 0,25 A	< 0,45 A	< 0,3 A	< 0,45 A	< 0,3 A	< 0,6 A	< 0,64 A	< 0,85 A	< 0,5 A	< 0,85 A	< 0,5 A	< 1 A	< 0,6 A	< 1 A	< 0,6 A	< 0,6 A	< 0,4 A
Alarme batterie faible	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%	10,5 V DC ± 3%	21 V DC ± 3%
Protection batteries faibles	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%	9,5 V DC ± 3%	19 V DC ± 3%
Protection surtension	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC	≥ 15 V DC	≥ 30 V DC
Protection thermique	-												60°C ± 5°C									
Fusibles (A)	25	15	2 x 20	2 x 10	2 x 40	2 x 20	6 x 20	4 x 15	6 x 30	6 x 15	12 x 30	12 x 15	-									
Températures de travail	De 5°C à 35°C																					
Dimensions	152 x 103 x 61 mm		180 x 103 x 61 mm		230 x 100 x 60 mm		237 x 165 x 70 mm		260 x 165 x 70 mm		380 x 215 x 100 mm		205 x 202 x 70 mm		230 x 205 x 90 mm		316 x 205 x 95 mm				390 x 251 x 141 mm	
Poids	0.58 kg		0.76 kg		1.05 kg		1.88 kg		2.3 kg		6.09 kg		1.56 kg		2.25 kg		3.4 kg		3.56 kg		7.41 kg	

