



150 W



600 W



400 W



800 W



1700 W



1200 W



2500 W



4000 W

Convertisseurs de tension

12 / 220 V & 24 / 220 V





	① 150 W		② 400 W		③ 600 W		④ 800 W		⑤ 1200 W		⑥ 1700 W		⑦ 2500 W		⑧ 4000 W	
Volts (V)	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220	12 / 220	24 / 220
Référence	ACMA612	ACMA622	ACMA416	ACMA516	ACMA616	ACMA716	ACMA816	ACMA916	ACMA806	ACMA906	ACMA866	ACMA876	ACMA836	ACMA846	ACMA926	ACMA986
Courant de charge maxi	15 A	10 A	40 A	20 A	60 A	30 A	82 A	40 A	130 A	65 A	150 A	85 A	250 A	125 A	400 A	200 A
Courant en veille	< 0.2 A	< 0.2 A	< 0.36 A	< 0.2 A	< 0.5 A	< 0.35 A	< 0.5 A	< 0.4 A	< 0.4 A	< 0.2 A	< 0.6 A	< 0.28 A	< 0.7 A	< 0.6 A	< 0.95 A	< 0.85 A
Fréquence de sortie	50 HZ		50 HZ		50 HZ		50 HZ		50 HZ		50 HZ		50 HZ		50 ou 60 HZ	
Puissance de sortie en continu	150 W		400 W		600 W		800 W		1200 W		1500 W		2500 W		4000 W	
Puissance de sortie en pointe	300 W		800 W		1500 W		2000 W		2400 W		3000 W		5000 W		8000 W	
Rendement	90 %		90 %		85 ~ 90 %		85 ~ 90 %		85 ~ 90 %		85 ~ 90 %		85 ~ 90 %		85 ~ 90 %	
Coupure batterie faible	9.5 ± 0.5 V DC	19.5 ± 0.8 V DC	9.5 ± 0.5 V DC	19.5 ± 0.8 V DC	9.5 ± 0.5 V DC	19 ± 0.8 V DC	10 ± 0.5 V DC	19 ± 0.8 V DC	10 ± 0.5 V DC	20 ± 0.8 V DC	9.5 ± 0.5 V DC	20 ± 0.8 V DC	9.5 ± 0.5 V DC	20 ± 0.8 V DC	9.5 ± 0.5 V DC	20 ± 0.8 V DC
Alarme batterie faible	10 ± 0.5 V DC	20 ± 0.8 V DC	10 ± 0.5 V DC	20 ± 0.8 V DC	10 ± 0.5 V DC	20 ± 0.8 V DC	10.5 ± 0.5 V DC	20 ± 0.8 V DC	10.5 ± 0.5 V DC	21 ± 0.8 V DC	10 ± 0.5 V DC	21 ± 0.8 V DC	10 ± 0.5 V DC	21.5 ± 0.8 V DC	10 ± 0.5 V DC	21.5 ± 0.8 V DC
Protection thermique	60°C ± 5°C		60°C ± 5°C		60°C ± 5°C		60°C ± 5°C		60°C ± 5°C		60°C ± 5°C		60°C ± 5°C		60°C ± 5°C	
Protection inversion polarité	Oui (par fusible)		Oui (par fusible)		Oui (par fusible)		Oui (par fusible)		Oui (par fusible)		Oui (par fusible)		Oui (par fusible)		Oui (par fusible)	
Fusibles	15 A	10 A	25A sur câble (x2) 15A sur PAC (x1)	35A sur câble (x2) 10A sur PAC (x1)	25 A (x3)	20 A (x3)	25 A (x4)	20 A (x4)	35 A (x5)	20 A (x5)	30 A (x8)	15 A (x8)	30 A (x12)	15 A (x12)	30 A (x18)	15 A (x18)
Dimensions	165 x 94 x 69 mm		181 x 90 x 75 mm		213 x 200 x 70 mm		280 x 200 x 70 mm		320 x 210 x 85 mm		458 x 210 x 85 mm		430 x 210 x 159 mm		550 x 210 x 159 mm	
Poids	520 g		1.3 kg		2.0 kg		2.6 kg		3.9 kg		5.5 kg		8.7 kg		11.2 kg	
Alimentation USB	5 V DC 500 mA (max.)		5 V DC 500 mA (max.)		Non		Non		Non		Non		Non		Non	

